

MATERIALS:

- SPILL CONTAINMENT CABINET:
- 16GA STEEL MINIMUM (ALT "S" 16GA MINIMUM STAINLESS STEEL)
- MOUNTING BRACKETS: 1/4" X 2" STEEL FLAT BAR (ALT "S" S/S SCH 40 MIN)
- FILL AND DRAIN PIPE FITTINGS:

ALL STEEL, SCH 40 MIN (ALT "S" S/S SCH 40 MIN)

· LOCK TABS:

3/16" STEEL WITH ½"DIA PADLOCK HOLE (ALT "S" 3/16" STAINLESS STEEL)

· COATING:

"P" POWDERCOAT ZINC RICH EXPOXY INTERIOR AND EXTERIOR W/2ND EXT. POLYESTER (ALT "S" STAINLESS STEEL, NO COATING)

CAUTION

FLAMMABLE OR COMBUSTIBLE
LIQUIDS/VAPORS MAY BE
PRESENT. KEEP AWAY SPARKS,
FLAME, IGNITION SOURCES.
EXTINGUISH SMOKING MATERIALS.
FOR USE WITH PROPERLY VENTED
STORAGE VESSELS. KEEP DOOR
CLOSED AND LOCKED WHEN NOT
IN USE.

DATE

This drawing and design are proprietary to BAKER INDUSTRIES NORTHWEST, and may not be copied or duplicated in whole or in part without the written permission of BAKER INDUSTRIES NW.

CHECKED



#700 SERIES GROUND LEVEL SPILL CONTAINMENT TANK MOUNTING BRACKT MODELS

BAKER INDUSTRIES NORTHWEST

12428 Highway 99 South, Unit 56
Everett, Washington 98204-5502
Tel:(425)212-3169 • FAX:(425)353-6788 • e-mail: larry@bakerindnw.com
www.bakerindustriesnorthwest.com

	REV	LRG	RBW	03-28-95
	REV	SLG	LRG	03-05-06
	REV			

DRAWN